

Motion detector

IS 2300 ECO

EAN 4007841034726

Order Code: **034726**



Functional description

The more obscure building corners, the more winding corridors and passageways, the more corner specialist IS 2300 ECO has what it takes. The 3 pyro sensors work together to give it a coverage angle of no less than 300°. So this little gem can even look round corners, quite literally. It's also a powerful performer in terms of switching capacity. At 2,000 watts, you can reliably automate lighting systems made up of several luminaires all

Technical specifications

Model	Motion sensor
Sensor type	Passive infrared
Accessories	Includes corner wall mount for external and internal corners
Detection angle	300° with 90° angle of aperture (directional head ±80° swivel adjustment)
Sneak by guard	Yes
Reach, tangential	r = 12m (377m ²)
Application	Indoors/Outdoors
Installation	Wall corner, surface
Recommended mounting height	2m
Dimensions (w x h x d):	85 x 60 x 95mm
Voltage	230-240 V/50 Hz
max. output (ohmic loads, ie., all incandescent lamps)	2000 W
max. output	max. 8 (electronic ballast / LED lamps) C ≤ 176 µf
Capability of masking out individual segments	Yes
Sensor system	456 switching zones
Twilight setting	2 - 2000 Lux
Time setting	10 sec. - 15 min.
Degree of protection (IP) / Protection class	IP54 / II
Temperature	-20-50 °C
Version	Black, RAL 9005
Warranty	5 years

Motion detector

IS 2300 ECO

EAN 4007841034726

Order Code: **034726**

Sensors Detection Range

