



EZN006

Multifunction timer

Architecture	
Fixing mode	DIN rail type O (symmetrical)
Functions	
Switching cycles	min. 50000
- Functions: On delay, Off delay, single shot leading edge/single shot trailing edge, pulse shaping, flashing symmetrically, contact open/closed	
Configuration	
- change-over contact, usable as NC or NO	
Main electrical features	
Nominal voltage	12 ... 48 V=/12 ... 230 V~
Frequency	50/60 Hz
Electric current	
Max. power with cos phi 0.6	5 A
Switching current at cos ? = 0.6	max. 5 A
Power	
Power consumed	15 VA
Power consumption (operation)	15 VA
Total power loss under IN	2 W
Loss power at full load	~ 2 W
Power dissipation per coil	0,5 W
Dimensions	
Depth of installed product	58 mm
Height of installed product	85 mm
Length	64 mm
Width of installed product	17,5 mm
Width of rail mounted device (RMD)	1 modules

Fluorescent bulbs control

Fluorescent lamps	max. 600 VA
-------------------	-------------

LED control

LED	with LED for operating status display
-----	---------------------------------------

Incandescent bulbs control

Max. power with incandescent lamps	450 W
230 V incandescent lamps and halogen lamps	max. 450 W

Installation, mounting

Mounting type	din-Rail
Installation mode	for mounting on DIN rail

Connection

Connection cross-sect. flexible conductor	1 / 6mm ²
Connection cross-sect. rigid cable	1,5 / 10mm ²
Conductor cross-section (flexible)	1 6 mm ²
Conductor cross-section (rigid)	1,5 10 mm ²
Number of contacts	1
Type of contacts	1 changeover
Type of connection	with screw
- with screw terminals	

Settings

Time delayed range	0.1 s... 10 h
Delay time, adjustable	0,1 s 10 h
- with 2 potentiometers for setting of delay time	

Safety

Protection index IP	IP40
---------------------	------

Use conditions

Operating temperature	-20 50 °C
Storage/transport temperature	-40 70 °C

Instructions

- Notice:

Not suitable for connection to safety extra-low voltage (SELV).