

Similar image
(Picture shows SVN391)

Impulse 1NO + 1NC Double Pushbutton

Main electrical features

Rated operational voltage Ue	230 V
Frequency	50/60 Hz

Voltage

Rated insulation voltage	250 V
Rated impulse withstand voltage	4000 V
Switching voltage	230 V

Electric current

Rated current	16 A
Momentary-contact current	16 A
Prospective short circuit withstand with MCB 16A B curve	1000A [Prot:16AcurveB]
Prospective short circuit withstand with fuse 16A gG	1000A [Prot:16AgG]
Thermal rated current outside of housings	16 A

Endurance

Electric endurance in number of cycles	15000
Number of mechanical operations	15000

Materials

Colour	not applicable

Dimensions

Depth of installed product	66 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

Installation, mounting

Tightening torque	1,7Nm

Connection

Connection cross-sect. flexible conductor	0,75 / 6mm²
Connection cross-sect. rigid cable	0,75 / 10mm²
Type of connection	with screw

Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1

Standards

European directive WEEE	not concerned

Safety

Protection index IP	IP20

Use conditions

Operating temperature	-20 50 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	3
Altitude	2000 m
Storage/transport temperature	-40 80 °C