

6 M Surface mounting enclosure IC2 EGY

VD106PT

Architecture	
Fixing mode	surface-mounting
Functions	
With a pipe-in lead	yes
Compatibility	
Compatible with DIN rail mounting	yes
Main electrical features	
Nominal voltage	400 V
Electric current	
Rated current	63 A
Cover, door	
Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	Closed (plain)
Door locking	without
Door leave	single
Door quantity	1
Cover type	Door
Transparent cover or door	no
Materials	
Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

Dimensions

Depth of installed product	91 mm
Internal depth	72 mm
Height of installed product	170 mm
Width of installed product	134,5 mm
Width in division units	6

Installation, mounting

Suitable for outdoor use	no

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	yes
Extension possible	no

Standards

GWT Glow wire test	650 °C
European directive WEEE	not concerned

Safety

IK protection code against mecanical impacts	IK07
Protection index IP	IP40
Protection class	isol.class II
Halogen free	yes
Ultraviolet resistant	no

Use conditions

Operating temperature	-25 40 °C