

Similar image
(Picture shows VE312F)

vector, IP65,48M, UV-stable, DC/AC

| | |
|---|---|
| **Architecture** | |
| Fixing mode | surface-mounting |
| **Functions** | |
| With a pipe-in lead | yes |
| **Compatibility** | |
| Compatible with DIN rail mounting | yes |
| **Main electrical features** | |
| Nominal voltage | 400 V |
| **Electric current** | |
| Rated current | 63 A |
| **Cover, door** | |
| Type of door closing | Latch |
| Identification od protection index | 65 |
| Interlockable | no |
| Cover type | Closed (plain) |
| Door locking | without |
| Door leave | single |
| Door quantity | 1 |
| Cover type | Door |
| Transparent cover or door | yes |
| **Materials** | |
| Colour | light grey |
| Colour | light grey |
| RAL colour | RAL 7035 - Light grey |
| Material | plastic |
| Type of surface treatment | untreated |

### Dimensions

| | |
|---|---|
| Depth of installed product | 151 mm |
| Internal depth | 151 mm |
| Height of installed product | 677 mm |
| Width of installed product | 310 mm |
| Width in division units | 48 |
| Thickness of sidewall material | 2,5 mm |

### Installation, mounting

| | |
|---|---|
| Suitable for outdoor use | yes |

### Connection

| | |
|---|---|
| Number of conduit inlets | 12 |

### Accessories included

| | |
|---|---|
| Mounting plate included | no |
| With lock | no |

### Equipment

| | |
|---|---|
| Number of rows | 4 |
| Quantity of section in width | 1 |
| Quantity of rails | 4 |
| Can be accessorized | yes |
| Number of openings for flange plates | 46 |
| Extension possible | no |

### Standards

| | |
|---|---|
| European directive WEEE | concerned |

### Safety

| | |
|---|---|
| IK protection code against mecanical impacts | IK08 |
| Protection index IP | IP65 |
| Protection class | isol.class II |
| Glow wire test | according EN 60695-2-11: 850°C |
| Halogen free | yes |
| Ultraviolet resistant | yes |

### Use conditions

| | |
|---|---|
| Operating temperature | -25  40 °C |