Sm.distr, golf, flush, 54M, white door DZA

VF318PT

Architecture

Fixing mode	flush-mounting

Functions

With a pipe-in lead	yes

Compatibility

Compatible with DIN rail mounting	yes

Main electrical features

Nominal voltage	400 V

Electric current

Rated current	80 A

Cover, door

Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	Closed (plain)
Door locking	without
Door leave	single
Door quantity	1
Cover type	Door
Transparent cover or door	no

Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

Dimensions

Insertion depth	72 mm
Depth of installed product	97,5 mm
Internal depth	97,5 mm
Height of installed product	543 mm
Width of installed product	460 mm
Width in division units	18
Built-in height	507 mm
Built-in width	426 mm

Installation, mounting

Suitable for outdoor use	no

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of rows	3
Quantity of section in width	1
Quantity of rails	3
Can be accessorized	yes
Extension possible	yes

Safety

Protection index IP	IP40
Protection class	isol.class II
Halogen free	yes
Ultraviolet resistant	no

Use conditions

Operating temperature	-25 40 °C