Industrial Suspended/Surface Mount
LEDE Select 150W High Bay

SPECIFICATIONS

DIMENSIONS	*D340 x H110mm*
COLOUR TEMP	*4000K Natural White or 5700K Daylight*
LUMENS	*77W / 14,000lm* *96W / 17,000lm* *111W / 19,500lm* *132W / 23,000lm* ***150W / 25,500lm (default factory setting)***
CRI	*80*
LIFESPAN	*57,000 hours (L80 B10)*
BEAM ANGLE	*90°*
MATERIAL	*Aluminium / PC*
IP RATING	*IP65*
IK RATING	*IK08*
DRIVER	*Incorporated, modular quick release plug and play driver pre-wired with 1500mm lead and three pin plug.*
FLICKER	*≤ 3% at 100Hz, Pst≤1.0; SVM ≤4 at Full Load to avoid stroboscopic effect in rotating machinery*
DIMMING	*Individually Dimmable to 10% (in 5% intervals) via remote control when installed with plug and play sensor accessory*
SENSOR	*Motion and Daylight sensor accessory available. Remote adjustable power output, detection area, hold time, daylight threshold, stand-by period and stand-by dimming level.* ***Default sensor factory settings:*** *Detection area: 100%, Hold time: 3min, Daylight threshold: 200 lux, Stand-by period: 10s, Stand-by dimming level: 50%.*
APPLICATION	*Industrial Highbay*
POWER FACTOR	*>0.90*
AMBIENT TEMP	*-30˚C to +50˚C*
WEIGHT	*2600g*
WARRANTY	*5 Year Warranty*

<25,500 LUMENS | **<150 WATTS** | **AC 240V**

AVAILABLE IN

DESCRIPTION	CODE
4000K, "Select" 5 lumen Adjustable Output Non-Dimmable driver pre-wired with 3 pin plug	P700 4KA
4000K, "Select" 5 lumen Adjustable Output Non-Dimmable driver pre-wired with 3 pin plug. 4 Pack.	P700 4KA4P
5700K, "Select" 5 lumen Adjustable Output Non-Dimmable driver pre-wired with 3 pin plug	P700 57KA

ACCESSORIES

DESCRIPTION	CODE
Sensor	P700 S1
Remote Control for Sensor, Digital Display	P700 R1
Glare Shield	P700 GS1
250mm Chain with Snap links	P458 CH
Surface Mount Bracket	P700 SMB

P700 INRUSH CURRENT 50A SURGE TIME 400µs

MCB Type	MCB B10	MCB B16	MCB B20	MCB B25
Max. connected lights	3	5	6	7
	MCB C10	MCB C16	MCB C20	MCB C25
	6	9	12	14