



SPECIFICATIONS

DIMENSIONS	D150 x H130mm
CUT OUT	Ø 130-140mm (suitable for retrofit applications)
COLOUR TEMP	3000K Warm White or 4000K Natural White
LUMENS	White: 3000K: 11W/1000lm, 15W/1350lm, 19W/1850lm 4000K: 11W/1010lm, 15W/1360lm, 19W/1870lm Black: 3000K: 11W/950lm, 15W/1280lm, 19W/1750lm 4000K: 11W/960lm, 15W/1290lm, 19W/1770lm (Default factory setting 19W)
CRI	90 (R9 <60)
LIFESPAN	60,000 hours (L80 B10)
BEAM ANGLE	60°
MATERIAL	Aluminium + PC + PMMA
IP RATING	IP54
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F / IC-4
DRIVER	DX Series Under Insulation Adjustable Output Dimmable Driver included (pre-wired) 260/350/450mA
COMPLETE WITH	Pre-wired with GL240 adaptor for easy loop in loop out configuration
WARRANTY	5 Year Warranty

<1870 LUMENS	<19 WATTS	AC 240V
----------------------------	-------------------------	--------------------

	Adjustable Output UID™ Dimmable Under Insulation Driver Included
--	--

	Choose 11W, 15W or 19W, adjustable via dipswitch on driver
--	---

select **W**

AVAILABLE IN

Selectable Triple Wattage

DESCRIPTION	CODE
White 3000K, "Select" Triple Wattage	R602 W3KA
White 4000K, "Select" Triple Wattage	R602 W4KA
Black 3000K, "Select" Triple Wattage	R602 B3KA
Black 4000K, "Select" Triple Wattage	R602 B4KA

90° wide beam R603 version available

Fixed Wattage/Output (End of line)

DESCRIPTION	CODE
Black, 3000K, 12W, 940lm	R602 B3K
White, 3000K, 12W, 970lm	R602 W3K
White, 4000K, 20W, 1850lm	R602 W4KHO



GL240
Adaptor included



Fits **130mm**
Cut Outs