
Exterior Recessed Effect Light
Mini Narrow Beam Curve Low Glare



SPECIFICATIONS

DIMENSIONS	*D50 x H30mm*
CUT OUT	*Ø 38mm*
COLOUR TEMP	*3000K Warm White*
CRI	*80*
LIFESPAN	*50,000 Hours*
BEAM ANGLE	*35°*
MATERIAL	*Aluminium, 316 STS or Copper*
IP RATING	*IP44*
CLASSIFICATION	*IC Rated*
CLEARANCE	*0mm, zero clearance required*
DRIVER	*Sold separately 350mA*
DIMMABLE	*Yes*
APPLICATION	*Exterior recess highlighter*
WARRANTY	*5 Year Warranty*

367 LUMENS | **3.3** WATTS | **350mA** SERIES



Driver sold separately, specify when ordering.

IMPORTANT:
1. Connection to live driver will permanently damage all lighting on circuit. Halcyon takes no responsibility for product failures from incorrect wiring.
2. Constant current LED fittings must be wired in series ensuring correct polarity. Incorrect polarity / wiring will cause permanent LED and/or driver failure.
3. Pulsing/flashing lighting indicates wiring fault or under/overloaded driver power off immediately.

AVAILABLE IN

DESCRIPTION	CODE
White 3000K	R744 W3
Black 3000K	R744 B3
Copper 3000K	R744 CO3
316 Stainless Steel 3000K	R744 STS3