Recessed Fixed Downlight Kit
LEDE Economy Select

SPECIFICATIONS

DIMENSIONS	*D86 x H53mm*
CUT OUT	*Ø 72mm*
COLOUR TEMP	*Selectable 3000K Warm White or 4000K Natural White*
LUMENS	**White:** *3000K Warm White 680lm* *4000K Natural White 700lm* **Black:** *3000K Warm White 570lm* *4000K Natural White 590lm*
CRI	*90*
LIFESPAN	*52,000 Hours (L90)*
BEAM ANGLE	*85°*
MATERIAL	*Aluminium, PC*
IP RATING	*IP44*
CLEARANCE	*25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.*
CLASSIFICATION	*IC-F Rated*
DRIVER	*Included (Pre-wired) Under Insulation Dimmable 260mA*
APPLICATION	*Residential / Commercial Interior*
WARRANTY	*5 Year Warranty*

<700 LUMENS | **8.5 WATTS** | **AC 240V**

UID™ Dimmable Under Insulation Driver Included

select CCT

AVAILABLE IN

DESCRIPTION	CODE
Black 3000K/4000K "Select" Dual Colour, Dimmable	R770 B34
White 3000K/4000K "Select" Dual Colour, Dimmable	R770 W34