

LEDE



SPECIFICATIONS

DIMENSIONS	D400 x H107mm
COLOUR TEMP	Selectable 3000K or 4000K
LUMENS	3000K: 12W/1410lm, 16W/1880lm, 24W/2738lm 4000K: 12W/1570lm, 16W/2100lm, 24W/3100lm (Default factory setting 4000K/24W)
CRI	80
LIFESPAN	60,000 hours (L90 B50)
BEAM ANGLE	120°
MATERIAL	PC
IP RATING	IP54
IMPACT RATING	IK10
DRIVER	Incorporated, non-dimmable
ELECTRICAL CLASS	Class II - double insulated
APPLICATION	Interior Vertical or Horizontal Surface Mount
SENSOR	Sensor version configured for optional master/ slave grouping of sensor and non-sensor buttons. Default sensor factory settings: Detection Area: 100%, Hold Time: 1min, Stand-by Period: 10min (@20%), Daylight Sensor: Disabled. For detailed sensor specifications see online.
WARRANTY	5 Year Warranty

AVAILABLE IN

DESCRIPTION	CODE
White, "Select" 3000K/4000K, Triple Wattage	LED365 W34A
White, "Select" 3000K/4000K, Triple Wattage, Sensor	LED365 W34AS



Suitable for multiple wiring configurations the LED365 also features dual side knockouts and dual rear cable glands.

select CCT

select W

<3100
LUMENS<24
WATTSAC
240V

LEDE Commercial Buttons are modular in design, meaning all components are easily replaced quickly and with minimal waste. Hinged diode board and driver can be easily unplugged, removed and replaced. Ideal for retirement homes or easy maintenance for 24/7 commercial operations. See plug & play spare parts below for more details.




PLUG & PLAY SPARE PARTS


DESCRIPTION	CODE
Replacement diffuser	LED365 DIFF
Replacement LED & driver module 3K/4K	LED365 34RBDM
Replacement Sensor, LED & driver module 3K/4K	LED365 34RBDMS
Replacement driver	LED365 DR



LED365 DIFF



LED365 34RBDM



LED365 DR