



SPECIFICATIONS

DIMENSIONS	D150 x H130mm
CUT OUT	Ø 130-140mm (suitable for retrofit applications)
COLOUR TEMP	3000K Warm White or 4000K Natural White
LUMENS	White: 3000K: 11W/1050lm, 19W/1700lm 4000K: 11W/1070lm, 19W/1730lm Black: 3000K: 11W/ 715lm, 19W/ 1150lm 4000K: 11W/ 725lm, 19W/ 1175lm Default factory setting 19W
CRI	90
LIFESPAN	60,000 hours (L80 B10)
BEAM ANGLE	90°
MATERIAL	Aluminium + PC
IP RATING	IP54
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F / IC-4
DRIVER	DX Series Under Insulation Adjustable Output Dimmable Driver Included (pre-wired) 350/600mA
COMPLETE WITH	Pre-wired with GL240 adaptor for easy loop in loop out configuration
WARRANTY	5 Year Warranty

<1730
LUMENS

<19
WATTS

AC
240V



Adjustable Output
UID™ Dimmable Under
Insulation Driver Included



Choose 11W or 19W, adjustable
via dipswitch on driver

AVAILABLE IN

select **W**

DESCRIPTION	CODE
White 3000K, "Select" 11W/19W	R603 W3K
White 4000K, "Select" 11W/19W	R603 W4K
Black 3000K, "Select" 11W/19W	R603 B3K
Black 4000K, "Select" 11W/19W	R603 B4K

X-low glare 60° beam version available R602



GL240
Adaptor included

RETROFIT

Fits **130mm**
Cut Outs