

Exterior Recessed Fixed Downlight Kit
X-low Glare Retrospec Design Standard Series

R730



SPECIFICATIONS	
DIMENSIONS	D93 x H104mm
CUT OUT	Ø 72-82mm
COLOUR TEMP	3000K Warm White
LUMENS	White: 840lm Black, Copper & 316 STS: 770lm
CRI	90 (R9 <66)
LIFESPAN	60,000 (L80 B30)
BEAM ANGLE	50°
MATERIAL	316 Stainless Steel or Copper + Silicone sealing gasket
IP RATING	IP65 (front face only)
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F / IC-4
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired), 230mA
APPLICATION	Exterior
WARRANTY	5 Year Warranty

**<840
LUMENS**

**9.5
WATTS**

**AC
240V**

UID™ Dimmable Under Insulation Driver Included

AVAILABLE IN	
DESCRIPTION	CODE
White 316 STS 3000K	R730 XW3K
Black 316 STS 3000K	R730 XB3K
Brushed 316 STS 3000K	R730 XSTS3K
Copper 3000K	R730 XCO3K

RETROFIT

Fits **72-82mm**
Cut Outs