


Sprout



X461 350mm **X462** 750mm

Exterior Bollard



Specifications

Dimensions	Light Module Ø100mm. Base Ø90mm. H350 or 750mm.
Input	240V AC or 24V DC Constant Voltage
Watts	12W
Colour Temp	3000K
Lumens	600lm
CRI	>80
Lifespan	50,000hrs (L80 B10)
Beam Angle	360°
Binning	3-step SDCM
Finish	Black
Material	ADC12, 6063 Aluminium, PC
IP Rating	IP65
IK Rating	IK08
Driver	240V AC: Incorporated, non-dimmable or Dali Dimmable 24V DC: Driver sold separately, dimmable
TLAs	240V AC: "Flicker-free", Pst≤1.0; SVM ≤0.4
Electrical Class	240V AC: Class I luminaire, requires earth 24V DC: Class III
Application	Exterior
Working Temp	-30°C...+45°C
Warranty	5 Year Warranty




Black

Optional Accessories

Description	Code
J-Bolt Anchor Kit	X470-JBA
Landscape Spike	X470-SP

Coating Technical Detail

1000 hours salt spray tested.
Corrosivity Category as per ISO 12944-2
C4 - High (15 to 25 years).
C5 - Medium (7 to 15 years)



Available In

Description	Code
X461	
350mm, Non-dimmable, 240V AC	X461-B3K-360D-AC
350mm, Dali Dimmable, 240V AC	X461-B3K-DD-360D-AC
350mm, Dimmable, 24V DC (driver sold separately)	X461-B3K-D-360D-DC
X462	
750mm, Non-dimmable, 240V AC	X462-B3K-360D-AC
750mm, Dali Dimmable, 240V AC	X462-B3K-DD-360D-AC
750mm, Dimmable, 24V DC (driver sold separately)	X462-B3K-D-360D-DC

Dimensions

