



LT-TFP-15W


15W/m <1790lm/m

15
W/m

<1790
lm/m

67
IP

24V
CV



Cut Increments
Free-cut (1mm increments)

Tape Width
10mm

Tape Height
5mm

Specifications

Input	24V DC Constant Voltage
Wattage/m	14.4W
Colour Temp	3000K or 4000K
CRI	90
Lumens/m	1725lm@3000K, 1790lm@4000K
Lifespan	60,000hrs (L80 B50)
Binning	SDCM2
Beam Angle	120°
Diodes/m	160
Current Draw/m	0.6A
Max Run	<10m, see installation sheet
Mounting	Supplied with 3M adhesive backing
IP Rating	IP67
Driver	Sold separately, specify according to wattage/current x length
Application	Interior, Exterior
Warranty	5 Year Warranty

Available In

Description	Code
Custom Length	
IP67, 3000K (m)	LT-TFP-15W-3K-X
IP67, 4000K (m)	LT-TFP-15W-4K-X

Custom Feeds & Joins

Made-to-order feeds and joins, professionally soldered by Halcyon technicians. Specify the feed and join type to suit the application and installation constraints.

X-Rugged Feeds & Joins (IP67)

Heavy-duty, fully sealed solution for demanding environments. Featuring high flex/high temp silicone feed cable for maximum durability and protection.

X-Rugged Feeds White Silicone - 2 Core (Red/Black)

Description	Code
300mm	LTFXR-STD
1000mm	LTFXR-1000
3000mm	LTFXR-3000
5000mm	LTFXR-5000
10000mm	LTFXR-10000



X-Mini Feeds & Joins (IP65)

Compact, low-profile option designed for tight installations and slim extrusions where space is limited.

X-Mini Feeds 2 Core (Red/Black)

Description	Code
300mm	LTFX-STD
1000mm	LTFX-1000
3000mm	LTFX-3000
5000mm	LTFX-5000
10000mm	LTFX-10000



X-Rugged Joins White Silicone - 2 Core (Red/Black)

Description	Code
30mm	LTJXR-STD
100mm	LTJXR-100
1000mm	LTJXR-1000
3000mm	LTJXR-3000
5000mm	LTJXR-5000
10000mm	LTJXR-10000



X-Mini Joins 2 Core (Red/Black)

Description	Code
30mm	LTJX-STD
100mm	LTJX-100
1000mm	LTJX-1000
3000mm	LTJX-3000
5000mm	LTJX-5000
10000mm	LTJX-10000




Installation Note: X-Rugged feeds and joins are recommended for all exterior applications.


Compatible Profile Examples

X-Rugged feeds and joins are not compatible with all aluminium profiles due to the larger dimensions / feed cable. Always refer to the relevant Aluminium Profile specification sheet to confirm feed clearance and compatibility. See Aluminium Profile specification sheets for the complete range.

Compatible with X-Mini Feeds & Joins Only




XS1715 Medium Narrow with Heat Sink




XS2311 Medium Standard Shallow


Compatible with X-Rugged, X-Mini Feeds & Joins



XS2222 Corner Mount



XS3030 Corner Mount



XS3535 Large Standard

Compatible Controllers

Pair Linear Strip with wireless control accessories such as Casambi or Basic RF for increased functionality and control.

