



M60-T22 Type 22 - Dark Art Pendant Spot

Watts 9W / 260mA DC **Lumens** <760lm

Beam 36°





M60-T23 Type 23 - Dark Art Pendant Spot


Watts 12W / 350mA DC **Lumens** <1000lm

Beam 45°


Specifications

CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.


Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty



Dimensions



M60-T22



M60-T23





Pendants

M60 Pendants are compatible with all M60 trimless, recessed and surface mount frames.



Step 1: Choose Installation Frame

See pages 166-167 for frame details



	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø81 x H60mm	L153 x W81 x H60mm	L81 x W81 x H60mm	L153 x W81 x H60mm	Ø130xH58mm	Ø85xH130mm
Cut Out	Ø75mm	2x 75mm @ 72mm centres	Ø75mm	2x 75mm @ 72mm centres	Ø105mm	-
White Code	F60-RR-W	F60-RR2-W	F60-RSQ-W	F60-RSQ2-W	F60-TL-R	SF60-RR-W
Black Code	F60-RR-B	F60-RR2-B	F60-RSQ-B	F60-RSQ2-B		SF60-RR-B

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	Reflector Colour	CCT	- Beam
M60	- T22	- W (White), B (Black)	W (White), HGB (High Gloss Black), B (Black), S (Silver), G (Gold)	3K	- 36D
M60	- T23	- W (White), B (Black)	W (White), HGB (High Gloss Black), B (Black), S (Silver), G (Gold)	3K	- 45D

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M60-T22	DCC260-DX-12W	DCC180500-DD-1012W @ 260mA	DCC150500-CAS-712W @ 260mA
M60-T23	DCC350-DX-20W	DCC260700-DD-1625W @ 350mA	DCC150500-CAS-712W @ 350mA

Configuration Example: For a Recessed Single M60-T22 Dark Art Pendant Spot in White with a Silver Reflector and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Recessed Frame: F60-RR-W (2) Light Module: M60-T22-WS3K-36D (3) Dimmable Driver: DCC260-DX-12W.