



M60 Type 30 with Trimless Frame

M60-T30 Type 30 - Adjustable Spot


Watts 2x 6.5W / 2x 200mA DC **Lumens** <590lm

Beam 36° **Tilt/Rotate** 355°/355°


Specifications

CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty




Dimensions



Step 1: Choose Installation Frame

See pages 166-167 for frame details



	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø81 x H60mm	L153 x W81 x H60mm	L81 x W81 x H60mm	L153 x W81 x H60mm	Ø130xH58mm	Ø85xH130mm
Cut Out	Ø75mm	2x 75mm @ 72mm centres	Ø75mm	2x 75mm @ 72mm centres	Ø105mm	-
White Code	F60-RR-W	F60-RR2-W	F60-RSQ-W	F60-RSQ2-W	F60-TL-R	SF60-RR-W
Black Code	F60-RR-B	F60-RR2-B	F60-RSQ-B	F60-RSQ2-B		SF60-RR-B

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	Reflector Colour	CCT	- Beam
M60	- T30	- W (White), B (Black)	W (White), HGB (High Gloss Black), B (Black), S (Silver), G (Gold)	3K	- 36D

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M60-T30	2x DCC200350-DX-815W@200mA	2x DCC150700-DDM-612W@200mA	2x DCC150500-CAS-712W@180mA

Configuration Example: For a Trimless M60-T30 Adjustable Spot in Black with a High Gloss Black Reflector and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Trimless Frame: F60-TL-R (2) Light Module: M60-T30-BHGB3K-36D (3) Dimmable Drivers: 2x DCC200350-DX-815W.