




M60 Type 7 with
Recessed Round Frame




M60 Type 7 with
Trimless Frame

M60-T7 Type 7 - Adjustable Highlighter

Watts 6.5W / 200mA DC **Lumens** 500lm

Beam 28° **Tilt/Rotate** 30° / 355°





M60 Type 10 with
Recessed Round Frame



M60 Type 10 with
Trimless Frame

M60-T10 Type 10 - Wallwasher

Watts 9W / 260mA DC **Lumens** 550lm

Beam 60°

Specifications


CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty


White


Black

Dimensions







M60-T7




M60-T10

Step 1: Choose Installation Frame

See pages 168-169 for frame details



	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø81 x H60mm	L153 x W81 x H60mm	L81 x W81 x H60mm	L153 x W81 x H60mm	Ø130xH58mm	Ø85xH130mm
Cut Out	Ø75mm	2x 75mm @ 72mm centres	Ø75mm	2x 75mm @ 72mm centres	Ø105mm	-
White Code	F60-RR-W	F60-RR2-W	F60-RSQ-W	F60-RSQ2-W	F60-TL-R	SF60-RR-W
Black Code	F60-RR-B	F60-RR2-B	F60-RSQ-B	F60-RSQ2-B		SF60-RR-B

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	CCT	- Beam
M60	- T7	- W (White), B (Black)	3K	- 28D
M60	- T10	- W (White), B (Black)	3K	

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M60-T7	DCC200350-DX-815W @ 200mA	DCC150700-DDM-612W @ 200mA	DCC150500-CAS-712W @ 180mA
M60-T10	DCC260-DX-12W	DCC180500-DD-1012W @ 260mA	DCC150500-CAS-712W @ 260mA

Configuration Example: For a Recessed Single M60-T7 Adjustable Highlighter in White and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Recessed Frame: F60-RR-W (2) Light Module: M60-T7-W3K-28D (3) Dimmable Driver: DCC200350-DX-815W.