



M61 Type 1 with
Recessed Square Frame



M61 Type 1 with
Trimless Square Frame

M61-T1 Type 1 - Dark Art Square Adjustable

Watts 6.5W / 200mA DC **Lumens** 560lm

Beam 38° **Tilt/Rotate** 20°/355°





M61 Type 2 with
Surface Square Box

M61-T2 Type 2 - Lotus Square Fixed

Watts 9W / 260mA DC **Lumens** 780lm

Beam 45°

Specifications


CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty




White/White | White/Black | Black/Black

Dimensions




M61-T1




M61-T2


Step 1: Choose Installation Frame


See pages 174-175 for frame details











	Recessed Square	Recessed Rectangular Double	Trimless Square	Trimless Rectangular Double	Surface Square Box
Dimensions	L82 x W82 x H52mm	L144 x W82 x H52mm	L130 x W130 x H55mm	L179 x W74 x H60mm	L78 x W78 x H125mm
Cut Out	75 x 75mm	135 x 75mm	105 x 105mm	140 x 75mm	-
White Code	F61-SQ-W	F61-SQ2-W	F61-TL-SQ	F61-TL-SQ2	SF61-SQ-W
Black Code	F61-SQ-B	F61-SQ2-B			SF61-SQ-B

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	Reflector Colour	CCT	- Beam
M61	- T1	- W (White), B (Black)		3K	- 38D
M61	- T2	- W (White), B (Black)	B (Black)	3K	- 45D

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M61-T1	DCC200350-DX-815W @ 200mA	DCC150700-DDM-612W @ 200mA	DCC150500-CAS-712W @ 180mA
M61-T2	DCC260-DX-12W	DCC180500-DD-1012W @ 260mA	DCC150500-CAS-712W @ 260mA

Configuration Example: For a Recessed Single M61-T1 Dark Art Square Adjustable in White and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Recessed Frame: F61-SQ-W (2) Light Module: M61-T1-W3K-38D (3) Dimmable Driver: DCC200350-DX-815W.