



M80 Type 11 with
Recessed Round Frame



M80 Type 11 with
Trimless Frame

M80-T11 Type 11 - Classico Fixed

Watts 12W / 350mA DC **Lumens** 1270lm

Beam 47°





M80 Type 12 with
Recessed Round Frame



M80 Type 12 with
Trimless Frame

M80-T12 Type 12 - Classico Adjustable

Watts 12W / 350mA DC **Lumens** 1260lm

Beam 47° **Tilt/Rotate** 15°/355°

Specifications


CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty


White


Black

Dimensions







M80-T11




M80-T12

Step 1: Choose Installation Frame

See pages 200-201 for frame details



	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø102 x H62mm	L192 x W102 x H62mm	L102 x W102 x H62mm	L192 x W102 x H62mm	Ø170 x H68mm	Ø106 x H146mm
Cut Out	Ø95mm	2x 95mm @ 90mm centres	Ø95mm	2x 95mm @ 90mm centres	Ø130mm	-
White Code	F80-RR-W	F80-RR2-W	F80-RSQ-W	F80-RSQ2-W	F80-TL-R	SF80-RR-W
Black Code	F80-RR-B	F80-RR2-B	F80-RSQ-B	F80-RSQ2-B	-	SF80-RR-B

Step 2: Choose Module Type

Model	- Type	- Reflector Colour	CCT	- Beam
M80	- T11	- W (White), B (Black)	3K	- 47D
M80	- T12	- W (White), B (Black)	3K	- 47D

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M80-T11	DCC350-DX-20W	DCC260700-DD-1625W @ 350mA	DCC260700-CAS-1325W @ 350mA
M80-T12	DCC350-DX-20W	DCC260700-DD-1625W @ 350mA	DCC260700-CAS-1325W @ 350mA

Configuration Example: For a Recessed Single M80-T11 Classico Fixed in White and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Recessed Frame: F80-RR-W (2) Light Module: M80-T11-W3K-47D (3) Dimmable Driver: DCC350-DX-20W.