



M80 Type 21 with Trimless Frame

M80-T21 Type 21 - Adjustable Spot

Watts 25W / 700mA DC **Lumens** <2500lm

Beam 36˚ **Tilt/Rotate** 90˚/355˚

Specifications


CCT	3000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty

White


Black





Dimensions




M80-T21

Step 1: Choose Installation Frame

See pages 200-201 for frame details



	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø102 x H62mm	L192 x W102 x H62mm	L102 x W102 x H62mm	L192 x W102 x H62mm	Ø170 x H68mm	Ø106 x H146mm
Cut Out	Ø95mm	2x 95mm @ 90mm centres	Ø95mm	2x 95mm @ 90mm centres	Ø130mm	-
White Code	F80-RR-W	F80-RR2-W	F80-RSQ-W	F80-RSQ2-W	F80-TL-R	SF80-RR-W
Black Code	F80-RR-B	F80-RR2-B	F80-RSQ-B	F80-RSQ2-B	-	SF80-RR-B

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	CCT	- Beam
M80	- T21	- W (White), B (Black)	3K	- 36D

Step 3: Select your Driver

	TRIAC Dimmable	Dali	Casambi
M80-T21	DCC700-DX-30W	DCC260700-DD-1625W @ 700mA	DCC260700-CAS-1325W @ 700mA

Configuration Example: For a Trimless Single M80-T21 Adjustable Spot in Black and a TRIAC Dimmable Driver, the following three components must be ordered. (1) Trimless Frame: F80-TL-R (2) Light Module: M80-T21-B3K-36D (3) Dimmable Driver: DCC700-DX-30W.