



S704 Shorty
Dimensions L200 x D90 x H41mm
Lumens 450lm
Watts 7W



S705 Standard
Dimensions L400 x D90 x H41mm
Lumens 640lm
Watts 10W



S706 Medium
Dimensions L600 x D90 x H41mm
Lumens 960lm
Watts 15W



S707 Long
Dimensions L900 x D90 x H41mm
Lumens 1280lm
Watts 20W



S708

Extra-Long

Dimensions L1200 x D90 x H41mm

Lumens 1920lm


Watts 30W

Specifications

Input	240V AC
Colour Temp	Selectable 3000K or 4000K
CRI	90
Lifespan	50,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 14
Beam	120°
Binning	3-Step SDCM
Material	Aluminium
IP Rating	IP44
Driver	Incorporated, dimmable
TLAs	"Flicker-free", Pst≤1.0; SVM ≤0.4
Installation	Interior, surface mount
Electrical Class	Class I luminaire, requires earth
Application	Interior only, multi-use surface mount wall
Warranty	5 Year Warranty




White



Black

Available In

Description	Code
S704	
White	S704-W34K-D
Black	S704-B34K-D
S705	
White	S705-W34K-D
Black	S705-B34K-D
S706	
White	S706-W34K-D
Black	S706-B34K-D
S707	
White	S707-W34K-D
Black	S707-B34K-D
S708	
White	S708-W34K-D
Black	S708-B34K-D



120 Degree
Wall Wash