



X471 250mm **X472** 600mm **X473** 1000mm



Specifications

Dimensions	Light module: Ø210mm. Pole: Ø60mm. H250, 600 or 1000mm
Input	240V AC or 24V DC Constant Voltage
Watts	240V AC: 24W, 24V DC: 10W
Colour Temp	3000K
Lumens	24W: 2090lm, 10W:907lm
CRI	>80
Lifespan	50,000hrs (L80 B10)
Beam Angle	360°
Binning	3-step SDCM
Finish	Black
Material	ADC12, 6063 Aluminium, PC
IP Rating	IP65
IK Rating	IK08
Driver	240V AC: Incorporated, non-dimmable 24V DC: Driver sold separately, dimmable
TLAs	240V AC: "Flicker-free", Pst≤1.0; SVM ≤0.4
Electrical Class	240V AC: Class I luminaire, requires earth 24V DC: Class III
Application	Exterior
Working Temp	-30°C...+45°C
Warranty	5 Year Warranty




Black

Optional Accessories

Description	Code
J-Bolt Anchor Kit	X470-JBA
Landscape Spike	X470-SP

Coating Technical Detail

1000 hours salt spray tested.
Corrosivity Category as per ISO 12944-2
C4 - High (15 to 25 years).
C5 - Medium (7 to 15 years)



Available In

Description	Code
X471	
250mm, Non-dimmable, 240V AC, 24W	X471-B3K-360D-AC
250mm, Dimmable, 24V DC, 10W (driver sold separately)	X471-B3K-D-360D-DC
X472	
600mm, Non-dimmable, 240V AC, 24W	X472-B3K-360D-AC
600mm, Dimmable, 24V DC, 10W (driver sold separately)	X472-B3K-D-360D-DC
X473	
1000mm, Non-dimmable, 240V AC, 24W	X473-B3K-360D-AC
1000mm, Dimmable, 24V DC, 10W (driver sold separately)	X473-B3K-D-360D-DC

Dimensions

