Inline Splice Red



Application

Tinned copper inline splice for secure, low-resistance electrical connections.

Design Specifications

- Material:
- Conductor: Brass Strip T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated




Compliance

- UL 486A-486B
- CSA C22.2 No.65-13
- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IEC 62321

General Information

Part No.	Type	Colour	Section (mm^2)	L (mm)	D (mm)	d (mm)	QTY	Packaging Type
HAMINSRD	Inline Splice Terminal	Red	0.5 - 1.5	24.5	4.3	1.7	100	Plastic Box



Logistic Information

Individual Packaging



x1

Basic Plastic Box
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.085
Gross Weight (kg): 0.125

Inner Box Packaging



x10

Carton Box
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 0.854
Gross Weight (kg): 1.381

Outer Box Packaging



x100

Carton Box
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 8.543
Gross Weight (kg): 14.043