Inline Splice Yellow DG

Application

Tinned copper inline splice for secure, low-resistance electrical connections.



Design Specifications

- Material:
- Conductor: Copper Strip T2/C11000
- Copper sleeve: Copper Tubular T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated
- With copper sleeve on barrel





Compliance

- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IE C62321

General Information

Part No.	Type	Colour	Section (mm^2)	L (mm)	D (mm)	d (mm)	QTY	Packaging Type
HAMINSYEDG	DG Inline Splice Terminal	Yellow	0.5 - 1.5	29.5	6.6	3.4	50	Plastic Box





Logistic Information

Individual Packaging



x1

Basic Plastic Box
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.149
Gross Weight (kg): 0.189

Inner Box Packaging



x10

Carton Box
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 1.489
Gross Weight (kg): 2.016

Outer Box Packaging



x100

Carton Box
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 14.892
Gross Weight (kg): 20.392