PVC Insulation Tape 19mm x 0.15mm Black 20m (8 Pack)



Application

PVC insulation tape for general electrical insulation, protection and identification. Made from plastic PVC with a synthetic rubber adhesive; flexible, pressure-sensitive, flame retardant, acid and alkali resistant, and lead-free.

Design Specifications

- Material: PVC Electrical Tape, Rubber Adhesive
- Dimensions: 19mm x 20m x 0.15mm.
- Tensile strength: > 28N/cm.
- Elongation at break: > 200%.
- Adhesion to steel 2B: 2.2N/cm.
- Adhesion to backing: 2.0N/cm.
- Dielectric strength: 45kV/mm.
- Insulation resistance: 1011Ω/25mm.
- Operating temperature: 0°C to +90°C.
- Application temperature: -10°C to +40°C.
- Application method: Recommended 50% overlap.
- Standards: EN 60454, IEC 60454-3-1-2002
- Colour: Black



Compliance

40046958

Comply With Standard EN60454-3-1 -2002

FLAME RETARDANT

RoHS COMPLIANT

General Information

Part No.	Colour	Length (m)	Width (mm)	Thickness (mm)	QTY	Packaging Type
HAMPIT1920BK	Black	20	19	0.15	8	Shrink Wrapped

Logistic Information

Individual Packaging

x1

Plastic Film
Heigth (cm): 16
Width (cm): 7.6
Depth (cm): 7.6
Net Weigth (kg): 0.65
Gross Weight (kg): 0.66

Outer Box Packaging

x15

Carton Box
Heigth (cm): 18
Width (cm): 40.5
Depth (cm): 24.5
Net Weigth (kg): 9.9
Gross Weight (kg): 10.5