# Quick Connector Female 6.4mm x 0.8mm Blue DG






## Application

Fully insulated female quick connector for safe and secure electrical connections.

## Design Specifications

- Material:
- Conductor: Brass Strip H62/C28000
- Copper sleeve: Copper Tubular T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated
- With copper sleeve on barrel


## Compliance

- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IEC 62321

## General Information

| Part No. | Type | Colour | Section ($mm^2$) | W (mm) | L (mm) | D (mm) | d1 (mm) | QTY | Packaging Type |
|---|---|---|---|---|---|---|---|---|---|
| HAMQCF64BL | DG Female Quick Connector | Blue | 1.5 - 2.5 | 6.6 | 21.5 | 4.7 | 2.3 | 100 | Plastic Box |






## Logistic Information

### Individual Packaging



x1

**Basic Plastic Box**
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.113
Gross Weight (kg): 0.153

### Inner Box Packaging



x10

**Carton Box**
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 1.134
Gross Weight (kg): 1.661

### Outer Box Packaging



x100

**Carton Box**
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 11.343
Gross Weight (kg): 16.843