Ring Terminal 3mm Hole Red



Application

Ideal for high-vibration or grounding applications where a reliable and accidental-disconnect-proof connection is required.

Design Specifications

- Material:
- Conductor: Copper Strip T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated




Compliance

- UL 486A-486B
- CSA C22.2 No.65-13
- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IEC 62321

General Information

Part No.	Type	Colour	Section (mm^2)	L (mm)	W (mm)	d1 (mm)	d2 (mm)	D (mm)	Thickness (mm)	QTY
HAMRT3RD	Ring Terminal	Red	0.5 - 1.5	18.7	5.5	1.7	3.2	4.0	0.75	100



Logistic Information

Individual Packaging



x1

Basic Plastic Box
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.062
Gross Weight (kg): 0.102

Inner Box Packaging



x10

Carton Box
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 0.618
Gross Weight (kg): 1.145

Outer Box Packaging



x100

Carton Box
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 6.180
Gross Weight (kg): 11.680