# Ring Terminal 3mm Hole Red DG



## Application

Ideal for high-vibration or grounding applications where a reliable and accidental-disconnect-proof connection is required.




## Design Specifications


- Material:
- Conductor: Copper Strip T2/C11000
- Copper sleeve: Copper Tubular T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated
- With copper sleeve on barrel

## Compliance

- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IEC 62321

## General Information

| Part No. | Type | Colour | Section ($mm^2$) | L (mm) | W (mm) | d1 (mm) | d2 (mm) | D (mm) | Thickness (mm) | QTY |
|---|---|---|---|---|---|---|---|---|---|---|
| HAMRT3RD DG | DG Ring Terminal | Red | 0.5 - 1.5 | 19.0 | 5.5 | 1.7 | 3.2 | 4.3 | 0.75 | 100 |




## Logistic Information

### Individual Packaging



x1

**Basic Plastic Box**
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.077
Gross Weight (kg): 0.117

### Inner Box Packaging



x10

**Carton Box**
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 0.772
Gross Weight (kg): 1.299

### Outer Box Packaging



x100

**Carton Box**
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 7.724
Gross Weight (kg): 13.224