Ring Terminal 5mm Hole Red DG



Application

Ideal for high-vibration or grounding applications where a reliable and accidental-disconnect-proof connection is required.

Design Specifications

- Material:
- Conductor: Copper Strip T2/C11000
- Copper sleeve: Copper Tubular T2/C11000
- Insulation: PVC
- Treatment: Tin-Plated
- With copper sleeve on barrel




Compliance

- EN 60998-1:2004
- (EU) 2015/863 (RoHS 2.0)
- EN 14362
- IEC 62321

General Information

Part No.	Type	Colour	Section (mm^2)	L (mm)	W (mm)	d1 (mm)	d2 (mm)	D (mm)	Thickness (mm)	QTY
HAMRT5RD DG	DG Ring Terminal	Red	0.5 - 1.5	22.0	8.0	1.7	5.3	4.3	0.75	100



Logistic Information

Individual Packaging



x1

Basic Plastic Box
Heigth (cm): 10.8
Width (cm): 8.1
Depth (cm): 3.6
Net Weigth (kg): 0.088
Gross Weight (kg): 0.128

Inner Box Packaging



x10

Carton Box
Heigth (cm): 19.0
Width (cm): 17.0
Depth (cm): 13.0
Net Weigth (kg): 0.878
Gross Weight (kg): 1.405

Outer Box Packaging



x100

Carton Box
Heigth (cm): 68.0
Width (cm): 36.0
Depth (cm): 21.0
Net Weigth (kg): 8.778
Gross Weight (kg): 14.278