# Thin Wall Heatshrink Tubing 1.5mm x 1.2m
No Glue



## Description

Thin wall 2/1 heatshrink tubing without adhesive.

## Application

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

## Design Specifications



- Thin wall, 2/1 shrinkage in length 1.2 meter.
- Heatshrink tubing in flexible flame retardant polyolefin (except clear).
- Working temperature: -45°C to +125°C (clear is -45°C to +105°C).
- Shrink temperature: 120°C (clear is 105°C).
- Dielectric strength (IEC 243): 15kV/mm.
- Tensile strength: 10.4Mpa.
- Rate voltage: 600V.
- Self-extinguishing in accordance with UL224 (except clear).

## General Information

| Part No. | Wall ø Before Shrinking (mm) | Wall ø After Shrinking (mm) | Length (mm) | Tensile Strength (daN) | Colour |
|---|---|---|---|---|---|
| HAMHSTW1508BK | 1.5 | 0.8 | 1200 | 104 | Black |
| HAMHSTW1508BL | 15 | 0.8 | 1200 | 104 | Blue |
| HAMHSTW1508GR | 1.5 | 0.8 | 1200 | 104 | Green |