



### Main

|                           |                         |
|---------------------------|-------------------------|
| Range                     | ClimaSys                |
| Product name              | ClimaSys CR             |
| Product or component type | Resistance heater       |
| Range compatibility       | P<br>G                  |
| Power range               | 55 W                    |
| Input voltage             | 110...250 V AC 50/60 Hz |

### Complementary

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Operating position                    | Vertical                                                                                                       |
| Ambient air temperature for operation | -40...70 °C                                                                                                    |
| IP degree of protection               | IP20                                                                                                           |
| Product certifications                | UL<br>VDE                                                                                                      |
| Material                              | Body: extruded aluminium                                                                                       |
| Height                                | 200 mm                                                                                                         |
| Width                                 | 85 mm                                                                                                          |
| Depth                                 | 70 mm                                                                                                          |
| Condition of use                      | Air sealed enclosure<br>Heaters must be installed with a thermal controller<br>Electrical protection is needed |
| Fixing mode                           | By clips                                                                                                       |
| Mounting support                      | 35 mm DIN rail                                                                                                 |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 534 g   |
| Package 1 Height             | 7 cm    |
| Package 1 width              | 8 cm    |
| Package 1 Length             | 20.5 cm |
| Unit Type of Package 2       | BB1     |
| Number of Units in Package 2 | 16      |
| Package 2 Weight             | 9.16 kg |
| Package 2 Height             | 16 cm   |
| Package 2 width              | 34 cm   |
| Package 2 Length             | 42 cm   |

Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#"> REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                                                                                                             |
| EU RoHS Directive          | Compliant <a href="#"> EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                             |
| RoHS exemption information | <a href="#"> Yes</a>                           |
| China RoHS Regulation      | <a href="#"> China RoHS Declaration</a>        |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins     |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|