# Product data sheet
## Characteristics

# NSYS3X8625
## SPACIAL S3X stainless 304L, Scotch Brite® finish, H800xW600xD250 mm.

## Main

| | |
|---|---|
| Range | Spacial |
| Product name | Spacial S3X |
| Enclosure type | Multi-purpose |
| Category | Compact enclosure |
| Nominal height | 800 mm |
| Nominal width | 600 mm |
| Nominal depth | 250 mm |
| Product installation | Wall-mounting |
| Device composition | 1 body<br>1 door<br>2 lock: door<br>2 perforated vertical profile drilled: door |

## Complementary

| | |
|---|---|
| Body type | Single piece body, cross-shaped structure<br>Gutter shaped front rail |
| Door type | Plain |
| Number of doors | Front face: 1 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 2 points lock, 3 mm double-bar |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Body and door: stainless steel 304L<br>Lock: zamak<br>Hinge: stainless steel |
| Surface finish | Body and door: Scotch-Brite® brushed<br>Lock: chromium plated |
| Net weight | 22.474 kg |

## Environment

| | |
|---|---|
| Standards | IEC 62208 |
| Product certifications | CAN/CSA 22<br>UL 508 type A |
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Environmental characteristic | Specific hygiene<br>Corrosive |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 21.444 kg |
| Package 1 Height | 26.5 cm |
| Package 1 width | 61 cm |
| Package 1 Length | 82 cm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |