



DIGITAL CLAMP METERS



CAT III
600V



**KLEIN.
TOOLS** 



MEASUREMENTS	CL120	CL220	CL320	CL390
True RMS	—	●	●	●
AC Voltage	600V	600V	600V	600V
DC Voltage	600V	600V	600V	600V
AC Current	400A	400A	400A	400A
DC Current	—	—	—	400A
AC Millivolts	●	●	●	●
DC Millivolts	●	●	●	●
DC Microamps	—	—	●	●
Ohms (Resistance)	20MΩ	20MΩ	40MΩ	40MΩ
Audible Continuity	●	●	●	●
Non-Contact Voltage Testing	●	●	●	●
Capacitance	—	—	4000µF	4000µF
Frequency	—	—	1 MHz	1 MHz
Frequency / Duty Cycle	—	—	●	●
Diode Test	—	—	●	●
Temperature °F (°C)	—	-40~1832°F (-40~1000°C)	-40~1832°F (-40~1000°C)	-40~1832°F (-40~1000°C)
Display Counts	2000	2000	4000	4000
CONVENIENCE				
Display	LCD with Backlight	LCD with Backlight	LCD with Backlight	LCD Reverse Contrast
MAX/MIN	MAX	MAX	MAX & MIN	MAX & MIN
Data Hold	●	●	●	●
Low Battery	●	●	●	●
Auto Power Off	15 Min	15 Min	15 Min	15 Min
Magnetic Hanger	Available as an Accessory	Available as an Accessory	Available as an Accessory	Available as an Accessory
Lead Holder on Clamp	●	●	●	●
DURABILITY				
Drop Protection	6.6 ft. (2m)	6.6 ft. (2m)	6.6 ft. (2m)	6.6 ft. (2m)
Safety Rating	Cat III 600V	Cat III 600V	Cat III 600V	Cat III 600V

Specifications Subject to Change

All Clamp Meters Include:

- Pouch
- Test leads with CAT III/CAT IV safety caps
- Thermocouple (Temperature measuring models only)
- 3 x AAA batteries
- User manual



CL120

400A AC CLAMP METER

Digital clamp meter measures AC current via the clamp; NCV with the sensor; AC/DC voltage, resistance, and continuity via test leads.



CL220

400A AC TRMS CLAMP METER WITH TEMPERATURE

Digital clamp meter with True Root-Mean Square (TRMS) measures AC current via the clamp; NCV with the sensor; AC/DC voltage, resistance, and continuity via test leads; and temperature via a thermocouple.





CL320

HVAC 400A AC TRMS CLAMP METER WITH TEMPERATURE AND DC MICRO AMP

Digital clamp meter with True Root-Mean Square (TRMS) measures AC current via the clamp; NCV with the sensor; AC/DC voltage, DC micro amps, resistance, capacitance, frequency, duty cycle, diode test, and continuity via test leads; and temperature via a thermocouple.



CL390

400A AC/DC TRMS CLAMP METER WITH TEMPERATURE AND DC MICRO AMP

Digital clamp meter with True Root-Mean Square (TRMS) measures AC/DC current via the clamp; NCV with the sensor; AC/DC voltage, DC micro amps, resistance, capacitance, frequency, duty cycle, diode test, and continuity via test leads; and temperature via a thermocouple.



Clamp Trigger

Large Jaw Size
1.38" (3.51 cm)

Meter shown
actual size.

NCV Sensing
Antenna detects
presence of
AC voltage

Arrow Markings
for optimal wire
placement

Test Lead Holder
for hands-free
operation

NCVT Light for
visual alarm of
AC voltage

Data HOLD
on/off button

Function Selection
Switch; functions
vary on models

NCV SEL Mode
on/off button

High Visibility
Display for
optimal viewability

Test Lead Input
Jacks; easy
access on front

Magnetic
Hanger Clips
onto Meter.
Available as
accessory.





CLAMP METERS

Cal. No.	UPC# 0-92644+	Description	Length	Width	Depth
CL120	69263-3	400A AC Clamp Meter	8.4" (213 cm)	3.5" (89 cm)	1.5" (3.8 cm)
CL120KIT	69264-0	Clamp Meter, Line Splitter, GFCI Tester	8.4" (213 cm)	3.5" (89 cm)	1.5" (3.8 cm)
CL220	69265-7	400A AC TRMS Clamp Meter with Temperature	8.4" (213 cm)	3.5" (89 cm)	1.5" (3.8 cm)
CL320	69266-4	HVAC 400A AC TRMS Clamp Meter with Temperature and DC Micro Amp	8.4" (213 cm)	3.5" (89 cm)	1.5" (3.8 cm)
CL390	69267-1	400A AC/DC TRMS Clamp Meter with Temperature and DC Micro Amp	8.4" (213 cm)	3.5" (89 cm)	1.5" (3.8 cm)



Line Splitter 10x 69409

Allows the measuring of current draw up to 15A without splitting the load's power cord



Test Lead Set, Right Angle 69410

Standard banana-type inputs compatible with most multimeters and clamp meters



Magnetic Hanger with Strap 69417

Powerful rare-earth magnet; durable nylon weave strap; fits all newer clamp meters



GFCI Receptacle Tester RT210

GFCI Outlet Tester with indicator lights, indicates common wiring problems



NEW! Magnetic Hanger no Strap 69445

Powerful rare-earth magnet; fits all newer clamp meters

ACCESSORIES AND REPLACEMENT PARTS

Cal. No.	UPC# 0-92644+	Description	Length	Width	Depth
69409	69409-7	Line Splitter 10x	4.7" (11.8 cm)	2.3" (5.8 cm)	4.7" (11.8 cm)
69410	69410-3	Test Lead Set, Right Angle	41" (10.4 cm)	0.6" (1.5 cm)	1.4" (3.5 cm)
69417	69417-2	Magnetic Hanger with Strap	5" (1.3 cm)	1" (2.4 cm)	5.6" (14.2 cm)
NEW 69445	69445-8	Magnetic Hanger no Strap	5" (1.3 cm)	1.3" (3.3 cm)	2.1" (5.3 cm)
RT210	69027-3	GFCI Receptacle Tester	2.9" (7.3 cm)	1.6" (4.1 cm)	1.9" (4.7 cm)



See our complete line of Test & Measurement Products
www.kleintools.com



© 2020 Klein Tools, Inc.
Livestock, IL 60069-1418
82 908 REV. 07/20 A

Code	Description
CL120	Klein CL120 400A AC Clamp Meter
CL220	Klein CL220 400A AC TRMS Clamp
CL320	Klein CL320 400A AC HVAC TRMS Clamp
CL390	Klein CL390 400A AC/DC TRMS Clamp