



Representative Photo Only
(actual product may vary based on configuration selections)

Mini Contactor 5A 2.2kW 3 pole 1N/O auxiliary 400...415V AC Coil

- Features low-profile design and 45mm width, permitting the use of enclosures with shallow mounting depths
- Accessories require no additional panel space
- Available in AC or DC control coil versions to suit your application requirements
- DIN rail mountable for easy installation

SPECIFICATIONS

Product Series	100-K05
Component Type Motor Control and Drives	Standard Contactor
Ie, Rated Operational Current, AC-1, 415V, 40°C	20 A@415V,40°C
kW Rating, AC-3, 415V, 60°C	2.2 kW @415V, 60°C
Ie, Rated Operational Current, AC-3, 415V, 60°C	4.9 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	2.2 kW @690V, 60°C
Ie, Rated Operational Current, AC-3, 690V, 60°C	2.8 A@690V,60°C
Number of Poles	3
Contact Configuration, Main Poles	3 NO main poles
Coil Type	Conventional type
Rated Frequency	50 / 60 Hz Hz
Un, Coil Voltage, AC @50Hz, Nom	400 V AC nom @50Hz
Un, Coil Voltage, AC @60Hz, Nom	400 V AC nom @60Hz
IP Rating	IP20

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-