Catalogue No: **100-K12DJ10**

CONTACTOR MINI 5.5kW 3P 24V DC COIL W/DIODE 1NO AUX

Motor Control and Drives > Motor Starting and Protection > Contactors > Allen-Bradley Contactors > Bulletin 100-K Miniature Contactors > 3-Pole Contactors with DC Coil

Representative Photo Only
(actual product may vary based on configuration selections)

Mini Contactor 12A 5.5kW 3 pole 1N/O auxiliary 24V DC Coil with diode

- Features low-profile design and 45mm width, permitting the use of enclosures with shallow mounting depths
- Accessories require no additional panel space
- Available in AC or DC control coil versions to suit your application requirements
- DIN rail mountable for easy installation

SPECIFICATIONS	
Product Series	100-K12
Component Type Motor Control and Drives	Standard Contactor
Ie, Rated Operational Current, AC-1, 415V, 40°C	20 A@415V,40°C
kW Rating, AC-3, 415V, 60°C	5.5 kW @415V, 60°C
Ie, Rated Operational Current, AC-3, 415V, 60°C	11.5 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	5.5 kW @690V, 60°C
Ie, Rated Operational Current, AC-3, 690V, 60°C	6.7 A@690V,60°C
Number of Poles	3
Contact Configuration, Main Poles	3 NO main poles
Contact Configuration, Auxiliary	1 NO auxiliary
Coil Type	Conventional w/ Integrated Diode type
Coil Voltage, DC, Nom	24 V DC
IP Rating	IP20

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-