Catalogue No: **1762-IQ16**

MLX1100/1200/1400 EXPANSION MODULE 16DI 24VDC SINK/SOURCE

Representative Photo Only
(actual product may vary based on configuration selections)

MicroLogix Digital Input Module 16 Point 24V DC Sink/Source

- Feature-rich functionality addresses a wide range of application
- Software keying prevents incorrect positioning within the syste
- Finger-safe terminal blocks for I/O wiring
- Small footprint reduces panel space

SPECIFICATIONS

Product Series	MicroLogix Expansion I/O (Bul. 1762)
Component Type PLC & I/O	Digital Input Module
Number of Digital Inputs	16 qty
Digital Input Type	24V DC Sinking/Sourcing type
Digital Input Range	10 ... 26.4V DC
Operating Temperature, Max	65 °C max
Operating Temperature, Min	-20 °C min
Relative Humidity, Max	95 %RH
Humidity type	Non-condensing
Shock Acceleration (Max.)	30 g
Vibration Acceleration (Max.)	5 g
Vibration Displacement (Peak to Peak Max.)	0.381 mm
Vibration Frequency, Operational (Max.)	500 Hz

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-