



Representative Photo Only
(actual product may vary based on configuration selections)

MicroLogix Expansion 4-Channel Analog Output Module, Voltage/Current

- Feature-rich functionality addresses a wide range of application
- Software keying prevents incorrect positioning within the syste
- Finger-safe terminal blocks for I/O wiring
- Small footprint reduces panel space

SPECIFICATIONS

Product Series	MicroLogix Expansion I/O (Bul. 1762)
Component Type PLC & I/O	Analogue Output Module
Number of Analogue Outputs	4 qty
Analogue Output Type(s)	Current / Voltage: Single-Ended
Analogue Output Range(s)	0 ... 10V DC 4 ... 20mA
Analogue Resolution, Output	12 bit (unsigned / unipolar)
Operating Temperature, Max	65 °C max
Operating Temperature, Min	-20 °C min
Relative Humidity, Max	95 %RH
Humidity type	Non-condensing
Shock Acceleration (Max.)	30 g
Vibration Acceleration (Max.)	5 g
Vibration Displacement (Peak to Peak Max.)	0.381 mm
Vibration Frequency, Operational (Max.)	500 Hz

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-