Catalogue No: **193-KB40**

OVERLOAD THERMAL 2.9-4A

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Allen-Bradley Overloads > Thermal (Bi-Metallic) Overloads > 193-K Thermal Overloads

Representative Photo Only
(actual product may vary based on configuration selections)

Mini Thermal Overload Relay, 2.9...4A, 1.5kW, for use with 100-K9...12, Trip Class 10A, Auto/Manual Reset

- Consistent and reliable protection for peace of mind
- Differential release for phase loss sensitivity and protection of motors in phase loss conditions
- Ambient temperature compensation from -20°C to +60°C for consistent performance

SPECIFICATIONS	
Component Type Motor Control and Drives	Thermal Overload
Adjustment	1.5 : 1
Current Range (A)	2.9...4.0
Approx kW	1.50
Details, Contactor	100-K05...12
Trip Class	10A
Reset	Automatic / Manual
Contact Configuration	1 NO + 1 NC
Test Function	Yes
Visible Trip Indicator	Yes
Motor FLC, Max	4 A, max
Motor FLC, Min	2.9 A, min
Rated Operation Voltage	690 V AC
IP Rating	IP20

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-