

Catalogue No: 194E-Y25M-1753-6N

ENCLOSED LBS BASE/DIN OFF-ON TYPE N ACT R/Y 3P 25A

Power Distribution and Protection > Isolators and Transfer Switches > Enclosed Isolating Switches > Allen-Bradley
Enclosed Isolating Switches > 194E Enclosed switches > Non-Metallic



Representative Photo Only
(actual product may vary based on configuration selections)

Enclosed poly carbonate grey color 194E switch with IP65 ratings
3P 25A

- IP66 / UL Type 1/3/3R/12 operating handles and high IP66 rated enclosures in polycarbonate, mild steel or stainless steel, has any environment, indoor or outdoor, covered.
- Suitable as At-Motor Disconnect Switch (UL508) useful for overseas application with added UL requirements
- 3 and 6 Pole enclosed switches dedicated to motor isolation and other load switch applications
- Padlockable handles available (up to 3 padlocks) for added security

SPECIFICATIONS

Product Series	Bul. 194E
Component Type Power Distribution & Protection	Enclosed Isolating Switch
Number of Poles	3
In, Rated Current	25 A
Un, Nominal Operational Voltage, AC	690 V AC
Ui, Rated Insulation Voltage	690 V (rms)
Rated Frequency	50 / 60 Hz Hz
Ie, Rated Operational Current, AC-21a, 240V	25 A@240V
Ie, Rated Operational Current, AC-21a, 690V	25 A@690V
Ie, Rated Operational Current, DC-21a, 24V, 1 Pole	25 A@24V
Ie, Rated Operational Current, DC-21a, 48V, 1 Pole	25 A@48V
Ie, Rated Operational Current, DC-21a, 110V, 1 Pole	5 A @110V
Ie, Rated Operational Current, DC-21a, 220V, 1 Pole	1 A @220V
Ie, Rated Operational Current, DC-21a, 440V, 1 Pole	0.5 A@440V
Ie, Rated Operational Current, DC-21a, 110V, 2 Pole	23 A@110V
Ie, Rated Operational Current, DC-21a, 220V, 2 Pole	5 A@220V
Ie, Rated Operational Current, DC-21a, 440V, 2 Pole	1 A@440V
Ie, Rated Operational Current, DC-21a, 600V, 2 Pole	0.6 A@600V
Ie, Rated Operational Current, DC-21a, 110V, 3 Pole	25 A@110V
Ie, Rated Operational Current, DC-21a, 220V, 3 Pole	13 A@220V
Ie, Rated Operational Current, DC-21a, 440V, 3 Pole	2.2 A@440V
Ie, Rated Operational Current, DC-21a, 600V, 3 Pole	1.5 A@600V
Current, Breaking Capacity AC23a, 230V	296 A
Current, Breaking Capacity AC23a, 400V	256 A
Current, Breaking Capacity AC23a, 690V	136 A
kW Rating, AC-23a, 230V, 1ph	7.5 kW
kW Rating, AC-23a, 400V, 3ph	11 kW @400V
kW Rating, AC-23a, 690V, 3ph	11 kW @690V

Catalogue No: **194E-Y25M-1753-6N**

ENCLOSED LBS BASE/DIN OFF-ON TYPE N ACT R/Y 3P 25A

Power Distribution and Protection > Isolators and Transfer Switches > Enclosed Isolating Switches > Allen-Bradley
Enclosed Isolating Switches > 194E Enclosed switches > Non-Metallic



Ith, Thermal Current	40 A
Uimp, Impulse Withstand Voltage, 1 min	8 kV, 1min
Current, Fuse-Protected Short-Circuit Capacity, 400V	20 kA
Icw, short time withstand current, 1s, 400V (rms)	900 kA for 1s
IP Rating	IP65
Material, Body / Housing	TP (Thermoplastic) material
Material, Handle	Plastic Handle
Colour, Body / Housing	Light Grey colour
Colour, Handle	Red colour
Wire / Conductor Size	2 x 1.5 mm ²
Wire / Conductor Size, Rigid Cable, Min	1.5 mm ²
Wire / Conductor Size, Rigid Cable, Max	6 mm ²
Mechanical service life	200000 cycles
Height	150 mm
Width	95 mm
Depth	86 mm
Standards Compliance	IEC 60947-3
Certifications	UL CSA CE

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-