Catalogue No: **800FP-U3F3F34**

PB 22.5mm 3P MOM M/F N/ILL F/GREEN F/GREEN RED

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Multifunction Momentary Pushbuttons > Plastic Body

3 FUNCTION PUSHBUTTON A =FLUSH GREEN / B= EXTENDED RED

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	800FP
Component Type Pushbutton and Pilot Lights	Multi-Function
Operator Type	Multi-Function Pushbutton, 3-Position type
Operator Type, Top	Pushbutton, Flush
Operator Type, Centre	Pushbutton, Extended
Operator Type, Bottom	Pushbutton, Flush
Operator Action, Position 1	Latched / Maintained
Operator Action, Position 3	Latched / Maintained
Operator Action, Top	Momentary
Operator Action, Bottom	Momentary
Colour, Operator Position 1	Green
Colour, Operator Position 3	Red
Operator Colour, Top	Green
Operator Colour, Centre	Red
Operator Colour, Bottom	Red
Material, Operator Position 1	Polycarbonate & PBT Blend
Material, Operator Position 3	Polycarbonate & PBT Blend
Operator Material, Top	Polycarbonate & PBT Blend
Operator Material, Centre	Plastic
Operator Material, Bottom	Plastic
Operator Insert Top	Green insert
Operator Insert, Bottom	Green insert
Material, Bezel	Glass-Filled Nylon / PA6 / PA66 (Polyamide 6)
Coupling Plate Included	No Y / N
Contact Block Included	No
Illuminated (Centre Only)	No Y / N
Tightening Torque, Nominal	1.7 Nm
Mechanical service life	1000000 cycles

Catalogue No: 800FP-U3F3F34

PB 22.5mm 3P MOM M/F N/ILL F/GREEN F/GREEN RED

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Multifunction Momentary Pushbuttons > Plastic Body

RoHS Approved	Yes
CE Marked	Yes
Operating Temperature, Max	70 °C max
Operating Temperature, Min	-25 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative humidity, min	50 %RH
Relative Humidity, Max	95 %RH
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 g
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	180 min
Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850
Certifications	UR UL CSA CCC CE RoHS
Shipping Approvals	ABS (American Bureau of Shipping)

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	800F_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	800F_Manufacturer Catalogue