



LIFELINE-32 NC + 1 NO

- Models available for a wire span of up to 125m
- Includes universal mounting and operation
- Includes lid mounted emergency stop button, designed to conform to ISO 850
- Provides switch lockout on cable pulled and cable slack
- Includes cable status indicator on switch lid
- Stainless steel 316 version available

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Safety	Pull Wire Switch
Safety Performance Level(s) (ISO13849:2006)	ISO 13849:2006 PLd ISO 13849:2006 PLe
Safety Performance Level	PLd, PLe safety
SIL Rating(s) (IEC/EN 61508)	IEC/EN 61508 SIL2 IEC/EN 61508
SIL Rating	SIL 2
SIL Claim(s) - Machinery (IEC/EN 62061)	IEC/EN 62061 SILCL3 IEC/EN 62061
SIL Claim, Machinery	SIL CL 3 machinery
Safety Category(s) (ISO13849:1999 / EN954)	EN 954 / ISO 13849:1999 Category 1 ISO 13849:1999
Safety Category	Cat 1 safety
Details, Safety	Suitable for use in Cat 3 or Cat 4 systems, B10d: > 2 x 10 ⁶ at min. load, PFHd: < 3 x 10 ⁻⁷
Output Configuration, Safety	2 NC
Output Configuration, Auxiliary	1 NO
E-Stop Button	No Y / N
Ith, Thermal Current	10 A
Ui, Rated Insulation Voltage	500 V (rms)
Ie, Rated Operational Current, AC-15, 120V	6 A@120V
Ie, Rated Operational Current, AC-15, 240V	3 A@240V
Ie, Rated Operational Current, AC-15, 600V	1.2 A@600V
Ie, Rated Operational Current, DC-13, 24V	2 A@24V
Ie, Rated Operational Current, DC-13, 600V	2 A@600V
Ex Rated	No
IP Rating	IP67
Material, Body / Housing	Zinc Alloy, Die-Cast, Painted material
Conduit Entry	M20 entry
Cable Entry Position	Top
Module Spacing, max	30 m

Catalogue No: **440E-D13100**

LIFELINE 3 PULL WIRE SWITCH 30M 2 NC 1 NO M20 CONDUIT

Safety > Safety Pushbuttons and Operator Devices > Safety Pull Wire Switches > Emergency Stop Pull-wire Switches > Lifeline 3



Colour, Cover	Yellow colour
Height	204 mm
Width	40 mm
Depth	56 mm
Weight	0.61 kg
Mechanical service life	1000000 cycles
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	80 °C max
Standards Compliance	IEC 60947-5-1 IEC 60947-5-5 ISO 13850 EN ISO 12100: 2010 IEC/EN 62061 SILCL3 ISO 13849:2006 PLd ISO 13849:2006 PLe EN 954 / ISO 13849:1999 Category 1
Certifications	CE CCC TUV PLe TUV PLd TUV SIL3 TUV SIL2

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-