

Catalogue No: **440G-S36001**

SPARTAN SWITCH PWR RLS 2NC 1NO 24V AC/DC

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley Mechanical Interlocks > Guard-Locking Interlock Switches > Spartan



Guard Locking Switch - 440G-MT: Solenoid Voltage: 24V AC/DC, Contacts(Safety and Aux): 2 Normally Closed, 1 Normally Open, Actuator: Standard, Conduit Entry: M20 Conduit



- Available in tongue-interlocking or solenoid-based guard interlocking types
- Heads are rotatable for optimum mounting flexibility
- Suitable for sliding, hinged or lift-off guards

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Safety Switch Type	Guard Locking Switch type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	1
Output Configuration, Auxiliary	1 NO
Holding Force, Max	1200 N
Conduit Entry	1 x M20 entry
Actuator Included	Yes Y / N
Actuator Type	Standard (fixed) tongue
Includes actuator guide	No Y / N
Un, Nominal Operational Voltage, AC	24 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Material, Body / Housing	Alloy, Die-Cast material
Ex Rated	No
IP Rating	IP67

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-