




Representative Photo Only
(actual product may vary based on configuration selections)

CSB flush mount loadcentre, 18way, transparent door

- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate))
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

SPECIFICATIONS

Product Series	CSB
Component Type Power Distribution & Protection	Loadcentre Enclosure
IP Rating	IP40
Number of Poles	18
MCB Type	DIN Profile
Material, Body / Housing	ABS material
Colour, Body / Housing	White colour
Material, door	White-ABS, Clear PC (PolyCarbonate)
Colour, Door	Clear / Transparent door
Ue, rated operational voltage, AC, 3ph, nom	415 V AC
Ue, rated operational voltage, AC, 1ph, nom	240 V AC
In, Rated Current	100 A
In, rated current, busbar comb, centre feed	130 A
In, rated current, busbar comb, end feed	80 A
Tunnels, neutral bar	9/3/3/3
Tunnels, earth bar	18
Mounting	Flush Mount
Height	267 mm
Width	412 mm
Depth	105 mm
Height, base	232 mm
Width, base	380 mm
Depth, Base	76 mm
Height, cover	267 mm
Width, cover	412 mm
Depth, cover	29 mm
Height, Cutout	213 mm
Width, Cutout	365 mm

Catalogue No: **CSB18FT**

LOADCENTRE 18 WAY DIN FLUSH TRANSPARENT DOOR

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Flush Mount Transparent Door



Earth and Neutral bar Rating	100A 16 mm tunnel terminals
Standards Compliance	AS/NZS 3439.3

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

