

# DTRD2030AI

NHP DIN-T Residual Current Breaker RCBO 10kA 1 Pole and Switched Neutral 20A C Curve 30mA Type AI



|                |                               |
|----------------|-------------------------------|
| Component type | Earth leakage circuit breaker |
| Range          | DIN-T RCD                     |
| Model          | N/A                           |
| Product status | New Item                      |

NHP’s DIN-T range of residual current devices (RCDs) are a high-performance electrical safety solution designed for commercial, industrial and mining applications. These RCDs offer a high level of selectivity, with sensitives including 10mA, 30mA, 100mA and 300mA, and types starting at Type A for general purpose applications through to Type F and B for more complex loads.

## ELECTRICAL

|                                                                 |              |
|-----------------------------------------------------------------|--------------|
| Rated current                                                   | 20 A         |
| Rated voltage                                                   | 240 V        |
| Rated leakage current                                           | 30 mA        |
| Frequency                                                       | 50/60 Hz     |
| Rated short-circuit breaking capacity according to AS/NZS 61009 | 10 kA        |
| Voltage type                                                    | AC           |
| Trip curve                                                      | C            |
| Rated impulse withstand voltage Uimp                            | 4 kV         |
| Leakage current type                                            | Other        |
| Tripping time                                                   | 300 ms       |
| Min. service voltage                                            | 110 V        |
| Max. operating voltage (Umax)                                   | 264 V        |
| Rated residual make/break capacity                              | 6000 A       |
| Protected neutral pole                                          | No           |
| Number of poles (total)                                         | 2            |
| Electrical life at Un, In (service cycles)                      | 10000 cycles |
| Type of electric connection                                     | Fork and pin |
| Isolator application                                            | Yes          |
| Rated insulation voltage Ui                                     | 500 V        |
| Concurrently switching neutral conductor                        | Yes          |

## CONSTRUCTION

|                                |          |
|--------------------------------|----------|
| Mounting method                | DIN rail |
| IP rating                      | IP40     |
| Number of protected poles      | 1        |
| Anti-nuisance tripping version | Yes      |

## MECHANICAL

|                                  |              |
|----------------------------------|--------------|
| Mechanical life (service cycles) | 20000 cycles |
| Disconnection characteristic     | Undelayed    |

# DTRD2030AI

NHP DIN-T Residual Current Breaker RCBO 10kA 1 Pole and Switched Neutral 20A C Curve 30mA Type AI



**DIN-T™**  
RESIDUAL CURRENT DEVICES

## MECHANICAL

|                                                 |                      |
|-------------------------------------------------|----------------------|
| Connectable conductor cross section solid-core  | 1-35 mm <sup>2</sup> |
| Connectable conductor cross section multi-wired | 1-35 mm <sup>2</sup> |
| Max. shock duration                             | 13 ms                |
| Max. shock acceleration                         | 25 g                 |
| Max. vibration frequency, operational           | 150 Hz               |

## DIMENSIONS

|                                     |        |
|-------------------------------------|--------|
| Depth                               | 75 mm  |
| Height                              | 85 mm  |
| Width                               | 35 mm  |
| Weight                              | 0.2 kg |
| Width in number of modular spacings | 2      |

## ENVIRONMENT

|                       |             |
|-----------------------|-------------|
| Operating temperature | -25...70 °C |
|-----------------------|-------------|

## RELATED PRODUCTS

### ACCESSORY



**Item No:** DTAAXAL


**Required:** No

**Description:** NHP DIN-T Accessory Auxiliary/Alarm 1 Changeover Contact suits DIN-T DTM and DTR

**Item No:** DTALBAX

**Required:** No

**Description:** NHP DIN-T LOCKDIN Auxiliary Filler 9mm, 18mm, 27mm Pack Qty 10 each



**Item No:** DTALDC

**Required:** No

**Description:** NHP DIN-T Lock Toggle Device 1P/2P MCB



**Item No:** DTALDTRD

**Required:** No

**Description:** NHP DIN-T LOCKDIN RCBO 2P DTRD



**Item No:** DTALPF

**Required:** No

**Description:** NHP DIN-T Accessory Pole Filler to suit 63mm 3P Strip 54mm 6x9mm Segments



**Item No:** DTASHT110415V

**Required:** No

**Description:** NHP DIN-T Accessory Shunt Trip 110-415 V AC/DC suits DIN-T DTM and DTR



**Item No:** DTASHT12110V

**Required:** No

**Description:** NHP DIN-T Accessory Shunt Trip 12-110 V AC/DC suits DIN-T DTM and DTR



**Item No:** DTAUVT240V

**Required:** No

**Description:** NHP DIN-T Accessory Undervoltage Trip 240 V AC/DC suits DIN-T DTM and DTR



**Item No:** DTAUVT24V

**Required:** No

**Description:** NHP DIN-T Accessory Undervoltage Trip 24 V AC/DC suits DIN-T DTM and DTR



**Item No:** DTLD

**Required:** No

**Description:** NHP DIN-T LOCKDIN Locking Device Removable Individual Piece 8mm



**Item No:** DTPF12

**Required:** No

**Description:** NHP DIN-T Accessory Pole Filler 12Pole Strip 216mm equals 24 x 9mm Segments



**Item No:** DTT9025PN

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Terminal Insulated 90 Degrees 25mm Pin

# DTRD2030AI

NHP DIN-T Residual Current Breaker RCBO 10kA 1 Pole and Switched Neutral 20A C Curve 30mA Type AI



**DIN-T™**  
RESIDUAL CURRENT DEVICES

## RELATED PRODUCTS

### ACCESSORY



**Item No:** DTTAX25PN

**Required:** No

**Description:** NHP DIN-T Accessory Terminal Axial Pin 25mm



**Item No:** DTTAX25SP

**Required:** No

**Description:** NHP DIN-T Accessory Terminal Axial Spade 25mm



**Item No:** DTTAX50PN

**Required:** No

**Description:** NHP DIN-T Accessory Terminal Axial Pin 50mm



**Item No:** DTTTLT25PN2

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Terminal Axial Pin 25mm Long Insulated



**Item No:** DTTTLT35LPN

**Required:** No


**Description:** NHP DIN-T Accessory Terminal Lateral Pin 35mm Long



**Item No:** DTTTLT35PN

**Required:** No

**Description:** NHP DIN-T Accessory Terminal Lateral Pin 35mm Short



**Item No:** ICL102

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Bus Comb 10 Way 1Pole N Pin Type 80A End Feed 130A Centre Feed



**Item No:** ICL562

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Bus Comb 56 Way 1Pole N Pin Type 80A End Feed 130A Centre Feed



**Item No:** ICL62

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Bus Comb 06 Way 1Pole N Pin Type 80A End Feed 130A Centre Feed



**Item No:** ICLEC23

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Busbar Comb Endcap for 2 and 3Pole ICL and 3 Auxiliary



**Item No:** ICLTOC

**Required:** No

**Description:** NHP DIN-T Miniature Circuit Breaker Busbar Comb Tee Off Cap Strip of 5