

AL URD Cables

AL URD CABLE 4x300

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: XDDG27AA004CXAA

Country Ref.: 4514

Al Conductors, XLPE insulation, Black PVC Sheath, 0.6/1 kV. Made to AS/NZS 4026

DESCRIPTION

Application

- Recommended for use in Underground Residential Distribution Systems.



STANDARDS

National AS/NZS 4026



Conductor flexibility
Stranded



Rated Voltage U₀/U (U_m)
0.6/1 (1.2) kV



Cable flexibility
Rigid



Max. conductor temp. in service
90 °C



U.V resistance
Yes

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/07/23 www.nexans.co.nz Page 1 / 2

CHARACTERISTICS

Construction characteristics

Conductor material	Aluminum
Insulation	XLPE
Outer sheath	PVC
Type of conductor	Sector-shaped, stranded
Conductor flexibility	Stranded
Conductor shape	Sector-shaped
Sheath colour	Black
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	4
Conductor cross-section	300 mm ²
Nominal overall diameter	60.2 mm
Approximate weight	4.87 kg/m
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Max. DC resistance of the conductor at 20°C (Ohm/km)	0.1
Rated Voltage U ₀ /U (Um)	0.6/ 1 (1.2) kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	90 °C
U.V resistance	Yes