CU Cantol

CU CANTOL 25

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: BDBC17AA001CXNA
Country Ref.: 4676

Cu conductor, XLPE insulated, Black PVC sheath. 0.6/1 kV. Made to AS/NZS 5000.1

DESCRIPTION

Application

- Industrial and commercial applications (predominantly)
- Some domestic applications
- For use in various situations to supply the main power from the point of supply (either single or three phase application) to buildings, equipment, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc. Commonly used in Power Authority work.

STANDARDS

National AS/NZS 5000.1

Conductor flexibility	Rated Voltage Uo/U (Um)	Cable flexibility	Max.conductor temp.in service	U.V resistance
Class 2	**0.6/ 1 (1.2) kV**	**Rigid**	**90 °C**	**Yes**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

CU Cantol

CU CANTOL 25

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

CHARACTERISTICS

Construction characteristics	
Conductor material	Copper
Type of conductor	Circular compacted stranded
Insulation	XLPE
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Sheath colour	Black
With Green/Yellow core	No
With smaller neutral conductor	No
Dimensional characteristics	
Conductor cross-section	25 mm²
Nominal overall diameter	10.9 mm
Gland Size (A2 or A2F)	20S
Approximate weight	0.31 kg/m
Neutral conductor section (when smaller)	- mm²
Number of cores	1
Electrical characteristics	
Max. DC resistance of the conductor at 20°C	0.727 Ohm/km
Permissible short circuit current conductor 1s	3.6 kA
Rated Voltage Uo/U (Um)	0.6/ 1 (1.2) kV
Mechanical characteristics	
Cable flexibility	Rigid
Usage characteristics	
Max. conductor temperature in service	90 °C
U.V resistance	Yes

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper/ALuminium conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section														
[mm²]	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al
25	160	-	129	-	124	-	192	-	156	-	140	-	64	

Air Spaced from Surface, Unenclosed

Air touching, unenclosed

Air enclosed

Buried direct

Buried in single-way duct

Buried in multi-way duct

Cable surrounded by thermal insulation, unenclosed

Note© Copyright Standards New Zealand 2012.Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Contact
Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature:30°C
- Soil Temperature:15°C
- Soil Thermal Resistivity:1.2 K.m/W
- Depth of Burial:0.5 m

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper conductor - Circular compacted stranded - Insulation XLPE Aluminum conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section														
[mm²]	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al
25	138	-	129	-	107	-	162	-	141	-	121	-	64	

Air Spaced from Surface, Unenclosed

Air touching, unenclosed

Air enclosed

Buried direct

Buried in single-way duct

Buried in multi-way duct

Cable surrounded by thermal insulation, unenclosed

Note© Copyright Standards New Zealand 2012. Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.