

Nexans Ref.: BDBC44AA001CXNA

Country Ref.: 4778

Cu conductor, XLPE insulated, Black PVC sheath. 0.6/1 kV. Made to AS/NZS 5000.1

DESCRIPTION

Application

- Industrial and commercial applications (predominantly)
- Some domestic applications
- For use in various situations to supply the main power from the point of supply (either single or three phase application) to buildings, equipment, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc. Commonly used in Power Authority work.



STANDARDS

National AS/NZS 5000.1



Conductor flexibility
Class 2



Rated Voltage Uo/U (Um)
0.6/1 (1.2) kV



Cable flexibility
Rigid



Max.conductor temp.in service
90 °C



U.V resistance
Yes

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Type of conductor	Circular compacted stranded
Insulation	XLPE
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Sheath colour	Black
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Conductor cross-section	150 mm ²
Nominal overall diameter	20.6 mm
Gland Size (A2 or A2F)	32
Approximate weight	1.55 kg/m
Neutral conductor section (when smaller)	- mm ²
Number of cores	1

Electrical characteristics

Max. DC resistance of the conductor at 20°C	0.124 Ohm/km
Permissible short circuit current conductor 1s	21.5 kA
Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	90 °C
U.V resistance	Yes

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper/ALuminium conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section [mm²]														
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al
150	495	385	413	320	362	281	514	398	429	333	391	303	-	-
	Air Spaced from Surface, Unenclosed			Air touching, unenclosed					Air enclosed					
	Buried direct			Buried in single-way duct					Buried in multi-way duct					
	Cable surrounded by thermal insulation, unenclosed													

Note © Copyright Standards New Zealand 2012. Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/07/23 www.nexans.co.nz Page 2 / 3

Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper conductor - Circular compacted stranded - Insulation XLPE Aluminum conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section [mm²]														
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al
150	443	344	413	320	325	252	428	332	383	296	342	266	-	-
	Air Spaced from Surface, Unenclosed			Air touching, unenclosed					Air enclosed					
	Buried direct			Buried in single-way duct					Buried in multi-way duct					
	Cable surrounded by thermal insulation, unenclosed													

Note© Copyright Standards New Zealand 2012. Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m