

Remolex Cables

CU REMOLEX 2X 1.5+1.5E 250M

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: CNHQ05A3002CXHF

Country Ref.: 4948.25

Cu Conductors, PVC insulation, Laid up, Black PVC sheath, 450/750 V. Made to AS/NZS 5000.2. Circular multicore with integral earth.

DESCRIPTION

Application

- Industrial, commercial and domestic applications
- Small mains cables.



STANDARDS

National AS/NZS 5000.2



Conductor flexibility
Class 2



Rated Voltage Uo/U (Um)
450 / 750 V



Cable flexibility
Rigid



Max.conductor temp.in service
75 °C



U.V resistance
Yes

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/07/23 www.nexans.co.nz Page 1 / 3

 Nexans

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	PVC
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Core identification	Red, Black, Green/Yellow
With Green/Yellow core	Yes
With smaller neutral conductor	No

Dimensional characteristics

Number of cores	3
Conductor cross-section	1.5 mm ²
Earth conductor cross section	1.5 mm ²
Nominal overall diameter	8.9 mm
Gland Size (A2 or A2F)	20S
Approximate weight	0.12 kg/m
Neutral conductor section (when smaller)	- mm ²

Electrical characteristics

Max. DC resistance of the conductor at 20°C (Ohm/km)	13.6
Rated Voltage U ₀ /U	450/750 V
Rated Voltage U ₀ /U (U _m)	450 / 750 V

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	75 °C
U.V resistance	Yes

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - THREE & FOUR CORE REMOLEX PVC

Copper conductor Circular stranded Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
1.5	18	17	16	20	20	9
 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed		 Air enclosed			
 Buried direct	 Buried in single-way duct		 Cable surrounded by thermal insulation, unenclosed			

Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 28/07/23 www.nexans.co.nz Page 2 / 3

has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz.

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m