

TPS - Single Core

CU TPS 1X 1.5 RD WH 1HM

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: AABP05A1001WTRD

Country Ref.: 6766.1

Cu Conductor, PVC insulation, PVC sheath. 450/750 V. Made to AS/NZS 5000.2

DESCRIPTION

Application

- Domestic, commercial and industrial general applications.
- Fixed applications



STANDARDS

National AS/NZS 5000.2

TPS - Single Core

CU TPS 1X 1.5 RD WH 1HM

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

CHARACTERISTICS

Construction characteristics

Colour	Red / white
Type of conductor	Circular, stranded
Conductor material	Copper
Insulation	PVC
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Sheath colour	White
With Green/Yellow core	No
With smaller neutral conductor	No

Dimensional characteristics

Conductor cross-section	1.5 mm ²
Nominal overall diameter	4.4 mm
Gland Size (A2 or A2F)	20S/16
Approximate weight	0.04 kg/m
Neutral conductor section (when smaller)	- mm ²
Number of cores	1

Electrical characteristics

Max. DC resistance of the conductor at 20°C (Ohm/km)	13.6
Rated Voltage U _o /U	450/750 V
Rated Voltage U _o /U (U _m)	450 / 750 V

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

Usage characteristics

Max. conductor temperature in service	75 °C
---------------------------------------	-------

TPS - Single Core

CU TPS 1X 1.5 RD WH 1HM

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - TPS - SINGLE CORE

Copper conductor Circular stranded (except 1 mm² which is solid) Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
1.5	24	18	21	31	29	25	9
 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed			 Air enclosed			
 Buried direct	 Buried in single-way duct			 Buried in multi-way duct			
 Cable surrounded by thermal insulation							

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - TPS - SINGLE CORE

Copper conductor Circular stranded (except 1 mm² which is solid) Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm ²]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
1.5	19	18	17	22	26	22	9
 Air Spaced from Surface, Unenclosed	 Air touching, unenclosed			 Air enclosed			
 Buried direct	 Buried in single-way duct			 Buried in multi-way duct			
 Cable surrounded by thermal insulation							